



Project: _____

Location: _____

Cat.No: _____

Type: _____

Lamps: _____ Qty: _____

Notes: _____

Ordering Guide

Example: DB14 A A0 12L E

Product Code	DB14	Aluminum Bollard	
Finish	A H	Black Bronze	
Optics	A0	Symmetric	
Wattage	12L 100I	9.5W LED 100W INC	*1 *1
Voltage	E	120V	

*1 Available in 120V (E) only.

Specifications

HOUSING:

356 HM high-strength, low-copper, proprietary cast aluminum alloy . Dome roof with die-cast aluminum louvers. Easy access to lamp. 5" dia. extruded aluminum with a wall thickness of 0.125". All non-ferrous fasteners prevent corrosion and ensure longer life.

FINISH:

Thermoset polyester powdercoat is electrostatically applied after a five-stage conversion cleaning process and bonded by heat fusion thermosetting. Laboratory tested for superior weatherability and fade resistance in accordance with ASTM B117 specifications. For larger projects where a custom color is required, contact the factory for more information.

OPTICAL ASSEMBLY:

Symmetric. Die-cast aluminum louvers with underside painted with highly reflective white powdercoat. Tempered glass globe.

LAMPING:

LED and Incandescent Medium Base A19.

ELECTRICAL ASSEMBLY:

LED is 2700K warm white, delivers 800 lumens and is dimmable. Lamp life rates at 25,000 hours. 120 volt only.

LED and Incandescent have 4kv rated medium base porcelain socket. Nickel-plated screw shell with center contact.

INSTALLATION & MOUNTING:

Tube is mounted to the base plate with three (3) 5/16-18 flat head allen key stainless steel tamper-resistant screws.

WARRANTY:

Three-year limited warranty.

CERTIFICATIONS:

ETL listed to U.S. safety standards for wet locations. cETL listed to Canadian safety standards for wet locations. Manufactured to ISO 9001:2008 Standards.

Height :

14" (36cm)

Width:

6" (15cm)

Bolt Circle:

3" (8 cm)

Anchor Rods:

Internal (3) 3/8" dia. x 8" long (1 cm x 20cm)

Base Diameter:

5" (13cm)

Max. Weight:

Powdercoat: 10 lbs

