
MORPHEUS III

FR-W1813-60L

60" Ceiling Fan







PRODUCT DESCRIPTION

With cutting-edge smart controls and a totally quiet DC motor, Morpheus is a sleek piece of luxury in a stylish two- or three-blade design. Like all our smart fans, Morpheus connects through Wi-Fi to our exclusive Modern Forms app, so it doesn't matter if you're five feet away or five hundred miles away- control is always in the palm of your hand. A powerful LED luminaire with artisan-crafted opal glass and thick aerodynamically soundless blades round out the design. Available in four amazing finishes.

- · 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Optional LED light kit included
- Includes remote control (GB comes a wall control)
- Optional wall control sold separately
- Compatible with Modern Forms app

AIRFLOW/ENERGY EFFICIENCY

Weighted-Average/High Airflow CFM: 2798/7490 Weighted-Average/High Energy Use (W): 13/31 **Estimated Yearly Energy Cost (\$):** Weighted-Average/High Efficiency (CFM/W): 211/243 Max RPM: 142

ORDER NUMBER

Model	Hous	sing	Blade			
	AS	Automotive Silver	AS	Automotive Silver		
FR-W1813-60L	GB	Gloss Black	GB	Gloss Black		
	GW	Gloss White	GW	Gloss White		

SPECIFICATIONS

Construction: Aluminum, ABS Blade: 12° Pitch, 60" sweep Downrod: .75"W x 4.5"H included

Mounting Slope: Up to 30° Wire: 80" **Hanging Weight:** 17 lbs **Total Power:** 50.5W

Standards: UL/cUL Wet Location listed, Title 24 JA8-2016

Compliant, Title 20, Energy Star rated

Motor Type: 125 x 10 sensorless DC motor

WIRELESS PERFORMANCE

Wi-Fi Range: Up to 150 ft* **Bluetooth Range:** Up to 150 ft*

LUMINAIRE PERFORMANCE

Light Source: LED Light Wattage: 19.5W Lumens/ Delivered Lumens: 1600/1142 Dimming: Integrated CRI:

Color Temperature: 3000K (2700K/3500K options available)

Rated Life: 50,000 hours

Example: FR-W1813-60L-GW

For 2700K add "-27"; for 3500K add "-35" before the finish: FR-W1813-60L-27-GW

*Results may vary based on application and surroundings.

*This fan comes uni-pack - blade select options are not available



The Modern Forms app synchronizes seamlessly with smart home devices you already own













modernforms.com Phone (800) 526.2588 (800) 526.2585

Headquarters/Eastern Distribution Center Central Distribution Center 44 Harbor Park Drive Port Washington, NY 11050

1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

MORPHEUS III

FR-W1813-60L

60" Ceiling Fan



OPTIONAL ACCESSORIES

OF HONAL ACCESSORIES				
Bluetooth Wall Control		F-WCBT	WT White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control.
Bluetooth Remote Control	MACCOUNT O	F-RCBT	WT White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with Moder Forms Smart Fans. Includes easy-to-install wall cradle and batteries.
Downrod		XF-12 12IN XF-18 18IN XF-24 24IN XF-36 36IN XF-48 48IN XF-60 60IN XF-72 72IN		All our downrods are .75 (in) and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.
Downrod Couplers		XF-I		Connects two downrods together.
Sloped Ceiling Kit		XF-SCK		Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.

Examples: Wall Control: F-WCBT-WT, Remote Control: F-RCBT-WT, Downrod: XF-12-BN, Downrod Coupler: XF-I-MB, Sloped Ceiling Kit: XF-SCK-MW

SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45° .

NOTE: Recommended maximum downrod length of 72" with 80" lead wire